

TRANSLATION STOP FOR USE IN POWER EQUIPMENT

Cross-Reference to Related Applications

This application claims the benefit of and priority from the following U.S.

5 Provisional Patent Applications: Serial No. 60/225,056, filed August 14, 2000, Serial
No. 60/225,057, filed August 14, 2000, Serial No. 60/225,058, filed August 14, 2000,
Serial No. 60/225,059, filed August 14, 2000, Serial No. 60/225,089, filed
August 14, 2000, Serial No. 60/225,094, filed August 14, 2000, Serial No. 60/225,169,
filed August 14, 2000, Serial No. 60/225,170, filed August 14, 2000, Serial
10 No. 60/225,200, filed August 14, 2000, Serial No. 60/225,201, filed August 14, 2000,
Serial No. 60/225,206, filed August 14, 2000, Serial No. 60/225,210, filed
August 14, 2000, Serial No. 60/225,211, filed August 14, 2000, and Serial
No. 60/225,212, filed August 14, 2000.

Field

15 The present invention relates to safety systems and more particularly to a safety
system that stops translational motion of a cutting tool in power equipment.

Background

Power equipment such as miter saws, chop saws and radial arm saws include
circular blades that move down onto or across a workpiece to cut the workpiece. The
20 blades, however, present a risk of injury to a user of the equipment as they move to make
a cut. Accordingly, those saws often include blade guards that physically block an
operator from making contact with the blade to minimize the risk of injury. In many

cases, guards effectively reduce the risk of injury, however, there are many instances where the nature of the operations to be performed precludes using a guard that completely blocks access to hazardous machine parts. For example, a user of a radial arm saw draws the blade toward him as he cuts workpiece. The user typically holds the workpiece with one hand while operating the saw with his other hand. In such a situation, the saw blade is at least partially exposed so that the blade can cut the workpiece. While the blade is at least partially exposed, the blade may accidentally contact the user's finger and the user may continue pulling the blade into his finger before he can react.

Brief Description of the Drawings

Fig. 1 is a schematic block diagram of a machine with a fast-acting safety system.

Fig. 2 is a schematic diagram of an exemplary safety system in the context of a machine having a circular blade.

Fig. 3 is a side elevation of a radial arm saw equipped with a safety system.

Fig. 4 is a side elevation of a miter saw or chop saw equipped with a safety system.

Detailed Description

A machine that may incorporate a safety system according to the present invention is shown schematically in Fig. 1 and indicated generally at 10. Machine 10 may be any of a variety of different machines adapted for cutting workpieces, such as wood, including a table saw, miter saw (chop saw), radial arm saw, circular saw, band saw, jointer, planer, etc. Machine 10 includes an operative structure 12 having a cutting tool 14 and a motor assembly 16 adapted to drive the cutting tool. Machine 10 also includes a safety system

18 configured to minimize the potential of a serious injury to a person using machine 10. Safety system 18 is adapted to detect the occurrence of one or more dangerous conditions during use of machine 10. If such a dangerous condition is detected, safety system 18 is adapted to engage operative structure 12 to limit any injury to the user caused by the dangerous condition.

Machine 10 also includes a suitable power source 20 to provide power to operative structure 12 and safety system 18. Power source 20 may be an external power source such as line current, or an internal power source such as a battery. Alternatively, power source 20 may include a combination of both external and internal power sources. Furthermore, power source 20 may include two or more separate power sources, each adapted to power different portions of machine 10.

It will be appreciated that operative structure 12 may take any one of many different forms, depending on the type of machine 10. For example, operative structure 12 may include a stationary housing configured to support motor assembly 16 in driving engagement with cutting tool 14. Alternatively, operative structure 12 may include a movable structure configured to carry cutting tool 14 between multiple operating positions. As a further alternative, operative structure 12 may include one or more transport mechanisms adapted to convey a workpiece toward and/or away from cutting tool 14.

Motor assembly 16 includes one or more motors adapted to drive cutting tool 14. The motors may be either directly or indirectly coupled to the cutting tool, and may also be adapted to drive workpiece transport mechanisms. Cutting tool 14 typically includes

one or more blades or other suitable cutting implements that are adapted to cut or remove portions from the workpieces. The particular form of cutting tool 14 will vary depending upon the various embodiments of machine 10. For example, in table saws, miter saws, circular saws and radial arm saws, cutting tool 14 will typically include one or more
5 circular rotating blades having a plurality of teeth disposed along the perimetrical edge of the blade. For a jointer or planer, the cutting tool typically includes a plurality of radially spaced-apart blades. For a band saw, the cutting tool includes an elongate, circuitous tooth-edged band.

Safety system 18 includes a detection subsystem 22, a reaction subsystem 24 and a control subsystem 26. Control subsystem 26 may be adapted to receive inputs from a variety of sources including detection subsystem 22, reaction subsystem 24, operative structure 12 and motor assembly 16. The control subsystem may also include one or more sensors adapted to monitor selected parameters of machine 10. In addition, control subsystem 26 typically includes one or more instruments operable by a user to control the
15 machine. The control subsystem is configured to control machine 10 in response to the inputs it receives.

Detection subsystem 22 is configured to detect one or more dangerous, or triggering, conditions during use of machine 10. For example, the detection subsystem may be configured to detect that a portion of the user's body is dangerously close to, or in
20 contact with, a portion of cutting tool 14. As another example, the detection subsystem may be configured to detect the rapid movement of a workpiece due to kickback by the cutting tool, as is described in U.S. Provisional Patent Application Serial No. 60/182,866,

filed February 16, 2000, the disclosure of which is herein incorporated by reference. In some embodiments, detection subsystem 22 may inform control subsystem 26 of the dangerous condition, which then activates reaction subsystem 24. In other embodiments, the detection subsystem may be adapted to activate the reaction subsystem directly.

5 Once activated in response to a dangerous condition, reaction subsystem 24 is configured to engage operative structure 12 quickly to prevent serious injury to the user. It will be appreciated that the particular action to be taken by reaction subsystem 24 will vary depending on the type of machine 10 and/or the dangerous condition that is detected. For example, reaction subsystem 24 may be configured to do one or more of the
10 following: stop the movement of cutting tool 14, disconnect motor assembly 16 from power source 20, place a barrier between the cutting tool and the user, or retract the cutting tool from its operating position, etc. The reaction subsystem may be configured to take a combination of steps to protect the user from serious injury. Placement of a barrier between the cutting tool and teeth is described in more detail in U.S. Provisional Patent
15 Application Serial No. 60/225,206, filed August 14, 2000, entitled "Cutting Tool Safety System," and U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Cutting Tool Safety System," the disclosures of which are herein incorporated by reference. Retraction of the cutting tool from its operating position is described in more detail in U.S. Provisional Patent Application Serial No. 60/225,089, filed
20 August 14, 2000, entitled "Retraction System For Use In Power Equipment," and U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Retraction System For Use In Power Equipment," the disclosures of which are herein incorporated by reference.

The configuration of reaction subsystem 24 typically will vary depending on which action(s) are taken. In the exemplary embodiment depicted in Fig. 1, reaction subsystem 24 is configured to stop the movement of cutting tool 14 and includes a brake mechanism 28, a biasing mechanism 30, a restraining mechanism 32, and a release mechanism 34. Brake mechanism 28 is adapted to engage operative structure 12 under the urging of biasing mechanism 30. During normal operation of machine 10, restraining mechanism 32 holds the brake mechanism out of engagement with the operative structure. However, upon receipt of an activation signal by reaction subsystem 24, the brake mechanism is released from the restraining mechanism by release mechanism 34, whereupon, the brake mechanism quickly engages at least a portion of the operative structure to bring the cutting tool to a stop.

It will be appreciated by those of skill in the art that the exemplary embodiment depicted in Fig. 1 and described above may be implemented in a variety of ways depending on the type and configuration of operative structure 12. Turning attention to Fig. 2, one example of the many possible implementations of safety system 18 is shown. System 18 is configured to engage an operative structure having a cutting tool in the form of a circular blade 40 mounted on a rotating shaft or arbor 42. Blade 40 includes a plurality of cutting teeth (not shown) disposed around the outer edge of the blade. As described in more detail below, braking mechanism 28 is adapted to engage the teeth of blade 40 and stop the rotation of the blade. U.S. Provisional Patent Application Serial No. 60/225,058, filed August 14, 2000, entitled "Table Saw With Improved Safety System," U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Table

Saw With Improved Safety System,” U.S. Provisional Patent Application Serial No. 60/225,057, filed August 14, 2000, entitled “Miter Saw With Improved Safety System,” and U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled “Miter Saw With Improved Safety System,” the disclosures of which are herein
5 incorporated by reference, describe safety system 18 in the context of particular types of machines 10.

In the exemplary implementation, detection subsystem 22 is adapted to detect the dangerous condition of the user coming into contact with blade 40. The detection subsystem includes a sensor assembly, such as contact detection plates 44 and 46,
10 capacitively coupled to blade 40 to detect any contact between the user’s body and the blade. Typically, the blade, or some larger portion of cutting tool 14 is electrically isolated from the remainder of machine 10. Alternatively, detection subsystem 22 may include a different sensor assembly configured to detect contact in other ways, such as optically, resistively, etc. In any event, the detection subsystem is adapted to transmit a
15 signal to control subsystem 26 when contact between the user and the blade is detected. Various exemplary embodiments and implementations of detection subsystem 22 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,200, filed August 14, 2000, entitled “Contact Detection System For Power Equipment,” U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled “Detection System For
20 Power Equipment,” U.S. Provisional Patent Application Serial No. 60/225,211, filed August 14, 2000, entitled “Apparatus And Method For Detecting Dangerous Conditions In Power Equipment,” and U.S. Patent Application Serial No. ____, filed August 13, 2001,

entitled "Apparatus And Method For Detection Dangerous Conditions In Power Equipment," the disclosures of which are herein incorporated by reference.

Control subsystem includes one or more instruments 48 that are operable by a user to control the motion of blade 40. Instruments 48 may include start/stop switches, speed controls, direction controls, etc. Control subsystem 26 also includes a logic controller 50 connected to receive the user's inputs via instruments 48. Logic controller 50 is also connected to receive a contact detection signal from detection subsystem 22. Further, the logic controller may be configured to receive inputs from other sources (not shown) such as blade motion sensors, workpiece sensors, etc. In any event, the logic controller is configured to control operative structure 12 in response to the user's inputs through instruments 48. However, upon receipt of a contact detection signal from detection subsystem 22, the logic controller overrides the control inputs from the user and activates reaction subsystem 24 to stop the motion of the blade. Various exemplary embodiments and implementations of control subsystem 26 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,059, filed August 14, 2000, entitled "Logic Control For Fast-Acting Safety System," U.S. Patent Application Serial No. ___, filed August 13, 2001, entitled "Logic Control For Fast-Acting Safety System," U.S. Provisional Patent Application Serial No. 60/225,094, filed August 14, 2000, entitled "Motion Detecting System For Use In Safety System For Power Equipment," and U.S. Patent Application Serial No. ___, filed August 13, 2001, entitled "Motion Detecting System For Use In A Safety System For Power Equipment," the disclosures of which are herein incorporated by reference.

In the exemplary implementation, brake mechanism 28 includes a pawl 60 mounted adjacent the edge of blade 40 and selectively moveable to engage and grip the teeth of the blade. Pawl 60 may be constructed of any suitable material adapted to engage and stop the blade. As one example, the pawl may be constructed of a relatively high strength thermoplastic material such as polycarbonate, ultrahigh molecular weight polyethylene (UHMW) or Acrylonitrile Butadiene Styrene (ABS), etc., or a metal such as aluminum, etc. It will be appreciated that the construction of pawl 60 will vary depending on the configuration of blade 40. In any event, the pawl is urged into the blade by a biasing mechanism in the form of a spring 66. In the illustrative embodiment shown in Fig. 2, pawl 60 is pivoted into the teeth of blade 40. It should be understood that sliding or rotary movement of pawl 60 may also be used. The spring is adapted to urge pawl 60 into the teeth of the blade with sufficient force to grip the blade and quickly bring it to a stop.

The pawl is held away from the edge of the blade by a restraining member in the form of a fusible member 70. The fusible member is constructed of a suitable material adapted to restrain the pawl against the bias of spring 66, and also adapted to melt under a determined electrical current density. Examples of suitable materials for fusible member 70 include NiChrome wire, stainless steel wire, etc. The fusible member is connected between the pawl and a contact mount 72. Preferably member 70 holds the pawl relatively close to the edge of the blade to reduce the distance pawl 60 must travel to engage blade 40. Positioning the pawl relatively close to the edge of the blade reduces the time required for the pawl to engage and stop the blade. Typically, the pawl is held

approximately 1/32-inch to 1/4-inch from the edge of the blade by fusible member 70, however other pawl-to-blade spacings may also be used within the scope of the invention.

Pawl 60 is released from its unactuated, or cocked, position to engage blade 40 by a release mechanism in the form of a firing subsystem 76. The firing subsystem is coupled to contact mount 72, and is configured to melt fusible member 70 by passing a surge of electrical current through the fusible member. Firing subsystem 76 is coupled to logic controller 50 and activated by a signal from the logic controller. When the logic controller receives a contact detection signal from detection subsystem 22, the logic controller sends an activation signal to firing subsystem 76, which melts fusible member 70, thereby releasing the pawl to stop the blade. Various exemplary embodiments and implementations of reaction subsystem 24 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,056, filed August 14, 2000, entitled "Firing Subsystem For Use In A Fast Acting Safety System," U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Firing Subsystem For Use In A Fast Acting Safety System," U.S. Provisional Patent Application Serial No. 60/225,170, filed August 14, 2000, entitled "Spring-Biased Brake Mechanism For Power Equipment," U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Spring-Biased Brake Mechanism For Power Equipment," U.S. Provisional Patent Application Serial No. 60/225,169, filed August 14, 2000, entitled "Brake Mechanism For Power Equipment," and U.S. Patent Application Serial No. ____, filed August 13, 2001, entitled "Brake Mechanism For Power Equipment," the disclosures of which are herein incorporated by reference.

It will be appreciated that activation of the brake mechanism will require the replacement of one or more portions of safety system 18. For example, pawl 60 and fusible member 70 typically must be replaced before the safety system is ready to be used again. Thus, it may be desirable to construct one or more portions of safety system 18 in a cartridge that can be easily replaced. For example, in the exemplary implementation depicted in Fig. 2, safety system 18 includes a replaceable cartridge 80 having a housing 82. Pawl 60, spring 66, fusible member 70 and contact mount 72 are all mounted within housing 82. Alternatively, other portions of safety system 18 may be mounted within the housing. In any event, after the reaction system has been activated, the safety system can be reset, such as by replacing cartridge 80. The portions of safety system 18 not mounted within the cartridge may be replaced separately or reused as appropriate. Various exemplary embodiments and implementations of a safety system using a replaceable cartridge are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,201, filed August 14, 2000, entitled "Replaceable Brake Mechanism For Power Equipment," U.S. Patent Application Serial No. _____, filed August 13, 2001, entitled "Replaceable Brake Mechanism For Power Equipment," U.S. Provisional Patent Application Serial No. 60/225,212, filed August 14, 2000, entitled "Brake Positioning System," and U.S. Patent Application Serial No. _____, filed August 13, 2001, entitled "Brake Positioning System," the disclosures of which are herein incorporated by reference. However, it should be noted that a cartridge is not required.

While one particular implementation of safety system 18 has been described, it will be appreciated that many variations and modifications are possible within the scope

of the invention. Many such variations and modifications are described in U.S. Provisional Patent Application Serial No. 60/182,866, filed February 16, 2000 and U.S. Provisional Patent Application Serial No. 60/157,340, filed October 1, 1999, the disclosures of which are herein incorporated by reference.

5 In the case of miter saws, chop saws, radial arm saws, and other power equipment in which a cutting tool moves down onto or across a workpiece to cut the workpiece, reaction subsystem 24 can include a system to stop the cutting tool from continuing to move down onto or across the workpiece. Stopping the translational motion of the cutting tool can minimize any injury from accidental contact between a user and the cutting tool.

10 Fig. 3 illustrates an exemplary implementation of a system to stop the translational motion of a cutting tool in the context of a radial arm saw 1100. Typically, radial arm saw 1100 includes a horizontal base 1102, a vertical support column 1104 extending upward from base 1102, and a guide arm 1106 that extends from column 1104 vertically spaced above base 1102. A carriage 1108 is slidably coupled to the underside of guide arm 1106. The bottom end of carriage 1108 is connected to a saw housing 1110 and to a motor assembly 1112, allowing a blade 1114 to be pulled across the base to cut workpieces (not shown) supported on the base. Radial arm saw 1106 is preferably equipped with a system as described above to stop the spinning of the blade, which includes a brake pawl 60 in a cartridge 82.

20 In use, a user grasps a handle 1116 on the saw and pulls the saw and blade across a workpiece on base 1102. In so doing, a user may accidentally pull the saw into contact with a misplaced finger or some other part of his body. Upon contact, brake pawl 60

works to stop the blade from spinning, but since the user may be pulling the saw toward his or her body when contact is detected, the saw may continue to move toward the user even after pawl 60 has stopped the blade. This continued movement may cause the stopped blade to be driven over a portion of the user's body (e.g., the user's hand), causing further injury. A system to stop the movement of the carriage and saw along the guide arm once contact is detected between the blade and the user's body addresses this issue.

It will be appreciated that there are a wide variety of ways to stop the sliding movement of bracket 1108 along arm 1106. Fig. 3 illustrates two examples. One example includes a pivoting wedge assembly 1118. Assembly 1118 includes a wedge or pawl 1120 pivotally coupled to guide bracket 1108. An actuator 1122 mounted on bracket 1108 is operatively coupled to the control and detection subsystems associated with brake pawl 60 and cartridge 82 so that when pawl 62 is released, actuator 1122 engages pawl 1120. During normal operation, actuator 1122 maintains the wedge spaced-apart from guide arm 1106. However, once contact between the blade and the user's body is detected, the detection system sends an actuation signal to actuator 1122. The signal sent to actuator 1122 may be the same signal that triggers the release of brake pawl 60, or it may be a different signal. In any event, upon receipt of the actuation signal, the actuator drives against wedge 1120, causing it to pivot into the guide arm, preventing further movement of the guide bracket forward along the guide arm. The wedge may be constructed or coated with a high friction material such as rubber, and/or may be configured with teeth, etc., to increase its braking action.

The other exemplary braking configuration illustrated in Fig. 3 includes a lockable spool assembly 1124. Assembly 1124 may be used in place of, or in addition to, wedge assembly 1118. In any event, the lockable spool assembly includes a spring-loaded spool 1126 mounted on support column 1104. One end of a tether or cable 1128 is attached to guide bracket 1108, while the other end is wound around spool 1126. As the user pulls the saw across the base, the spool unwinds, allowing the tether to extend. The spring-loading of the spool ensures that the spool maintains a slight tension on the tether and retracts the tether around the spool when the user pushes the saw back toward the support column. Assembly 1124 also includes a spool brake, such as pawl 1130, operatively coupled to the control and detection systems associated with brake pawl 60. Thus, when contact between the blade and the user's body is detected, an actuation signal is sent to the spool brake, causing the spool to lock. Once the spool locks, the tether prevents further movement of the saw away from support column 1104. In an alternative implementation of spool assembly 1124 not shown in Fig. 3, the lockable spool may be contained in, or placed adjacent to, cartridge 82, in which case the tether would run from the spool backward to support column 1104.

It will be appreciated that there are many alternative methods, devices, and configurations for stopping the travel of the guide bracket and the saw along the guide arm. Any one or more of these alternatives may be used in place of, or in addition to, the braking configurations illustrated in Fig. 3 and described above.

Fig. 4 illustrates an exemplary implementation of a system to stop the translational motion of a cutting tool in the context of a miter saw or chop saw 1150. It will be

understood that miter saw 1150 may be any type of miter saw including a simple miter saw, compound miter saw, sliding compound miter saw, etc. Typically, miter saw 1150 includes a base or stand 1152 adapted to hold the workpiece to be cut. A swing arm 1154 is pivotally coupled to base 1152 to allow the arm to pivot downward toward the base.

5 Attached to arm 1154 is a housing 1156 adapted to at least partially enclose a circular blade 1158. A motor assembly 1112 is coupled to the housing, and includes a rotating arbor 1160 on which the blade is mounted. Motor assembly 1112 includes a handle 1162 with a trigger (not shown) operable to run the saw. An optional blade guard (not shown) may extend from the bottom of housing 1156 to cover any portion of the blade exposed from the housing. A person uses miter saw 1150 by lifting the saw up, placing a workpiece on base 1152, and then bringing the saw down onto the workpiece to cut the workpiece.

15 Miter saw 1150 also preferably includes a brake pawl 60 in a cartridge 82 configured to stop the spinning of the blade, as described above. A saw blade spinning at several thousand revolutions per minute has substantial angular momentum. Thus, when the brake pawl engages and stops the blade, the angular momentum must be transferred to the brake. Because the swing arm of the miter saw is free to pivot in the direction of blade rotation, the angular momentum of the blade may be transferred to the swing arm when the blade is suddenly stopped, causing the swing arm to swing downward. This sudden and forceful downward movement of the swing arm may cause injury to the user if a portion of the user's body is beneath the blade.

There are many suitable means for preventing the sudden downward movement of the swing arm. For example, the pivotal connection between the swing arm and the base of the miter saw may be electrically lockable, for example using an electromagnetic leaf brake, to prevent the arm from pivoting. The signal to lock the connection may be provided by the detection system. Alternatively, a shock absorber, such as a gas discharge cylinder, may be connected between the swing arm and the base to limit the speed with which the swing arm can pivot relative to the base, as shown at 1180 in Fig. 4. This arrangement also serves to limit how far the blade moves between the time contact between the blade and user is detected, and the time the blade is stopped by the pawl. While there are many other ways of connecting the swing arm to the base to prevent sudden movement of the arm toward the base, most such arrangements transfer the angular momentum to the swing arm/base assembly. Depending on the weight and balance of the saw, the angular momentum may be sufficient to cause the entire saw to overturn. Therefore, it may be desirable to secure the base to a stable surface with clamps, bolts, etc.

Figure 4 shows one way to prevent the sudden downward movement of swing arm 1154. Swing arm 1154 includes a cam portion 1170 having a cam surface 1172. Cam portion 1170 may be integral with the swing arm and housing 1156. A stopping pawl 1174 is mounted to vertical support 1104 adjacent cam surface 1172, and an actuator 1176 is positioned adjacent pawl 1174. The actuator 1176 is operatively coupled to the control and detection subsystems associated with brake pawl 60 and cartridge 82 so that when pawl 62 is released, actuator 1176 engages pawl 1174. During normal operation,

actuator 1176 maintains the pawl spaced-apart from cam surface 1172. However, once contact between the blade and the user's body is detected, the detection system sends an actuation signal to actuator 1176, which may be the same or a different signal that triggers the release of brake pawl 60. In any event, upon receipt of the actuation signal, the actuator drives against pawl 1174, causing it to pivot into cam surface 1172, preventing further movement of the swing arm. Pawl 1174 may be constructed or coated with a high friction material such as rubber, and/or may be configured with teeth, etc., to increase its braking action. Cam portion 1170 may be modified so that it extends as far as possible from the point around which it pivots, in order to provide as great a moment arm as possible to help stop the downward motion of the swing arm.

The miter saw in Fig. 4 also includes a piston/cylinder 1180 connected between swing arm 1154 and base 1152. That piston/cylinder limits the speed with which the swing arm can pivot relative to the base, and can also serve to stop or limit the downward motion of the blade when accidental contact with the blade is detected.

There are many alternative methods, devices, and configurations for stopping the swing arm from moving down. Any one or more of these alternatives may be used in place of, or in addition to, the pawl and cam configuration illustrated in Fig. 4 and described above. What is important is to provide a mechanical stop to halt the downward motion of the swing arm when the blade contacts a user.

Industrial Applicability

The present invention is applicable to power equipment, and specifically to woodworking equipment such as miter saws, chop saws, radial arm saws, and other equipment that moves a cutting tool down onto or across a workpiece.

5 A system to stop the motion of a cutting tool may be used alone or in combination with other safety features to maximize the performance of an overall safety system. For example, such a system may be used with a system that quickly stops the rotation of a blade so that the blade simultaneously stops moving toward a user and stops rotating, as described above, or it may provide the primary protection.

10 It is believed that the disclosure set forth above encompasses multiple distinct inventions with independent utility. While each of these inventions has been disclosed in its preferred form, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and subcombinations of the various elements, features, functions and/or properties disclosed
15 herein. No single feature, function, element or property of the disclosed embodiments is essential to all of the disclosed inventions. Similarly, where the claims recite "a" or "a first" element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more
20 such elements.

It is believed that the following claims particularly point out certain combinations and subcombinations that are directed to one of the disclosed inventions and are novel

and non-obvious. Inventions embodied in other combinations and subcombinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are directed to a different invention or directed to
5 the same invention, whether different, broader, narrower or equal in scope to the original claims, are also regarded as included within the subject matter of the inventions of the present disclosure.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227